Problem D. Paimon Sorting

Paimon just invents a new sorting algorithm which looks much like *bubble sort*, with a few differences. It accepts a 1-indexed sequence A of length n and sorts it. Its pseudo-code is shown below.

Algorithm 1 The Sorting Algorithm

```
1: function SORT(A)
2:     for i ← 1 to n do          ▷ n is the number of elements in A
3:         for j ← 1 to n do
4:             if a_i < a_j then          ▷ a_i is the i-th element in A
5:                 Swap a_i and a_j
6:             end if
7:         end for
8:     end for
9: end function
```

If you don't believe this piece of algorithm can sort a sequence it will also be your task to prove it. Anyway here comes the question:

Given an integer sequence $A = a_1, a_2, \cdots, a_n$ of length n, for each of its prefix A_k of length k (that is, for each $1 \le k \le n$, consider the subsequence $A_k = a_1, a_2, \cdots, a_k$), count the number of swaps performed if we call SORT(A_k).

Input

There are multiple test cases. The first line of the input contains an integer T indicating the number of test cases. For each test case:

The first line contains an integer n ($1 \le n \le 10^5$) indicating the length of the sequence.

The second line contains n integers $a_1, a_2, \cdots, a_n$ ($1 \le a_i \le n$) indicating the given sequence.

It's guaranteed that the sum of n of all test cases will not exceed 10^6.

Output

For each test case output one line containing n integers $s_1, s_2, \cdots, s_n$ separated by a space, where s_i is the number of swaps performed if we call SORT(A_i).

Please, DO NOT output extra spaces at the end of each line or your solution may be considered incorrect!

Example

standard input	standard output
3 5 2 3 2 1 5 3 1 2 3 1 1	0 2 3 5 7 0 2 4 0