Problem J. Java2016

Input file:	java2016.in
Output file:	java2016.out
Time limit:	2 seconds
Memory limit:	256 megabytes

John likes to learn esoteric programming languages. Recently he discovered the probabilistic programming language Java2K. Built-in functions of Java2K have only a certain probability to do whatever you intend them to do.

The Java2K programming is very hard, so John designed a much simpler language for training: Java2016. Built-in operators of Java2016 are deterministic, while their operands are random. Each value in Java2016 is a positive integer in the range 0..255, inclusive.

Java2016 supports six operators of three precedencies:

$$\begin{aligned}
\langle\text{expression}\rangle &::= \langle\text{expression}\rangle \text{ `}\texttt{min}\text{'} \langle\text{sum}\rangle \mid \langle\text{expression}\rangle \text{ `}\texttt{max}\text{'} \langle\text{sum}\rangle \mid \langle\text{sum}\rangle \\
\langle\text{sum}\rangle &::= \langle\text{sum}\rangle \text{ `}\texttt{+}\text{'} \langle\text{term}\rangle \mid \langle\text{sum}\rangle \text{ `}\texttt{-}\text{'} \langle\text{term}\rangle \mid \langle\text{term}\rangle \\
\langle\text{term}\rangle &::= \langle\text{term}\rangle \text{ `}\texttt{*}\text{'} \langle\text{factor}\rangle \mid \langle\text{term}\rangle \text{ `}\texttt{/}\text{'} \langle\text{factor}\rangle \mid \langle\text{factor}\rangle \\
\langle\text{factor}\rangle &::= \text{`}\texttt{(}\text{'} \langle\text{expression}\rangle \text{ `}\texttt{)}\text{'} \mid \text{`}\texttt{?}\text{'} \mid \langle\text{macro}\rangle
\end{aligned}$$

Minimum (‘min’) and maximum (‘max’) operators are defined as usual. Addition (‘+’), subtraction (‘-’) and multiplication (‘*’) are defined modulo 256. The result of the division (‘/’) is rounded towards zero. If the divider is zero, the program crashes. The argument of the operator is a result of another operator, evenly distributed random value (‘?’), or macro substitution.

For instance, the probability that “?/?/?” is evaluated to zero is 98.2%, while the probability of the crash is 0.8%.

The Java2016 program consists of zero or more macro definitions, followed by the resulting expression. Each macro definition has a form of

$$\begin{aligned}
\langle\text{macrodef}\rangle &::= \langle\text{macro}\rangle \text{ `}\texttt{=}\text{'} \langle\text{expression}\rangle \\
\langle\text{macro}\rangle &::= \text{`}\texttt{a}\text{'} \ldots \text{`}\texttt{z}\text{'}
\end{aligned}$$

The macro should be defined before the first use. It may not be redefined. The macro is expanded to its definition on each use. For instance,

```
a = ?  max ?
(a max a) / a
```

is expanded to “((? max ?) max (? max ?)) / (? max ?)”.

John is going to add probabilistic constants to Java2016, so for each possible constant value he needs a program that successfully evaluates to this value with at least one-half probability. Crashes are counted toward failures.

Input

The input contains a single integer c — the target constant ($0 \le c \le 255$).

Output

Output a Java2016 program that successfully evaluates to constant c with probability no less than 1/2. The total length of the program should not exceed 256 characters (excluding spaces).

Examples

java2016.in	java2016.out
0	? /?/ ?
1	a = ? max ? (a max a) / a